

STANDARD TILE SPECIFICATIONS

SIZE 2'0" x 2'0" THICKNESS 5/16" (8MM) BINDER URETHANE

* CUSTOM THICKNESSES AVAILABLE



COLOURED EPDM GRANULATE

1MM TO 3MM

* THE COLOUR CONCENTRATION OF THE STANDARD TILE IS 20%

GATORLOC SPECIFICATIONS


TEST TYPE	ASTM	RESULTS
SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	60-80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	95%*-120%*
TENSILE STRENGTH	D-412	260-340 PSI
COMPRESSION SET	D-395	-4.8%
VOC EMISSIONS	D-5116	<0.5MG/M ²
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	PASSES, 150 PSI
DIE-C TEAR	D-624	80 MIN
SURFACES FLAMMABILITY	D-2859	PASS
COEFFICIENT OF FRICTION	D-1894-95	>0.8*

* VARIES BASED ON COLOUR

NOTE: PHYSICAL PROPERTIES CAN VARY BY PRODUCT TYPE.
INFORMATION ABOVE APPLIES TO THIS PRODUCT ONLY.



0201 Cobalt/Frost



0202 Sandstone



0203 Steel/Frost



0204 Midnight Black