

STANDARD ROLL SPECIFICATIONS

WIDTH* 4'0" **LENGTH*** 25'0" **WIDTH TOLERANCES** 48" CUT @ 48.5" +/- .24" **BINDER** URETHANE

* CUSTOM ROLL SIZES AVAILABLE

THICKNESS

1/8" (3MM), 1/4" (6.5MM), 5/16" (8MM), 3/8" (9.5MM), 1/2" (12.5MM)

COLOURED EPDM GRANULATE

1MM TO 3MM

* COLOUR CONCENTRATION OF A STANDARD ROLL IS 10%



GATORPRO SPECIFICATIONS


TEST TYPE	ASTM	RESULTS
SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	60-80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	95%*-120%*
TENSILE STRENGTH	D-412	260-340 PSI
COMPRESSION SET	D-395	-4.8%
VOC EMISSIONS	D-5116	<0.5MG/M ²
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	PASSES, 150 PSI
DIE-C TEAR	D-624	80 MIN
SURFACES FLAMMABILITY	D-2859	PASS
COEFFICIENT OF FRICTION	D-1894-95	>0.8*

* VARIES BASED ON COLOUR


NOTE: PHYSICAL PROPERTIES CAN VARY BY PRODUCT TYPE. INFORMATION ABOVE APPLIES TO THIS PRODUCT ONLY.




0101 Pitch Black




0102 Sky Blue



0103 Arctic Blue




0104 Sandstorm




0105 Forest Green



0106 Fog White



0107 Fire Red



0108 Canary Yellow